- (2) When the master or person responsible for the mobile unit not in distress or the person responsible for the land station determines that further help is necessary.
- (b) A station transmitting a distress alert relay in accordance with paragraph (a) of this section or §80.1121(c) must indicate that it is not itself in distress.

§ 80.1117 Procedure for receipt and acknowledgement of distress alerts.

- (a) Acknowledgement by digital selective calling of receipt of a distress alert in the terrestrial services must comply with CCIR Recommendation 541, which is incorporated by reference.
- (b) Acknowledgement through a satellite of receipt of a distress alert from a ship earth station must be sent immediately (see §80.1119).
- (c) Acknowledgement by radiotelephony of receipt of a distress alert from a ship station or a ship earth station must be given in the following form:
 - (1) The distress signal MAYDAY;
- (2) The call sign or other identification of the station sending the distress message, spoken three times;
- (3) The words THIS IS (or DE spoken as DELTA ECHO in case of language difficulties):
- (4) The call sign or other identification of the station acknowledging receipt, spoken three times;
- (5) The word RECEIVED (or RRR spoken as ROMEO ROMEO ROMEO in case of language difficulties);
 - (6) The distress signal MAYDAY.
- (d) The acknowledgement by directprinting telegraphy of receipt of a distress alert from a ship station must be given in the following form:
 - (1) The distress signal MAYDAY;
- (2) The call sign or other identification of the station sending the distress alert;
 - (3) The word DE;
- (4) The call sign or other identification of the station acknowledging receipt of the distress alert;
 - (5) The signal RRR;
 - (6) The distress signal MAYDAY.
- (e) The acknowledgement by directprinting telegraphy of receipt of a distress alert from a ship earth station must be given by the coast earth sta-

tion receiving the distress alert by retransmitting the ship station identity of the ship transmitting the distress alert.

§ 80.1119 Receipt and acknowledgement of distress alerts by coast stations and coast earth stations.

- (a) Coast stations that receive a distress alert should defer acknowledgement for a short interval so that receipt may be acknowledged by a Rescue Coordination Center. Where an acknowledgement is not forthcoming within 3 minutes, the coast station in receipt of distress alerts must ensure that they are routed to a Rescue Coordination Center as soon as possible. Coast stations must provide assistance for distress communications when requested to do so by the U.S. Coast Guard. (This subpart does not specify any radio watches for coast stations.)
- (b) Coast earth stations in receipt of distress alerts must ensure that they are routed as soon as possible to a Rescue Coordination Center. Coast earth stations must relay, as soon as possible, an acknowledgement of a distress alert from a Rescue Coordination Center.
- (c) Certain messages must be carried without charge, regardless of the means by which they are transmitted:
 - (1) Distress alert messages;
- (2) Search and rescue coordination messages;
- (3) Medical assistance messages where an imminent danger to life is present, or
- (4) Urgent meteorological or navigational danger messages passed in the ship-to-shore direction.

§ 80.1121 Receipt and acknowledgement of distress alerts by ship stations and ship earth stations.

- (a) Ship or ship earth stations that receive a distress alert must, as soon as possible, inform the master or person responsible for the ship of the contents of the distress alert.
- (b) In areas where reliable communications with one or more coast stations are practicable, ship stations in receipt of a distress alert should defer acknowledgement for a short interval so that receipt may be acknowledged by a coast station.

§80.1123

- (c) Ship stations operating in areas where reliable communications with a coast station are not practicable that receive a distress alert from a ship station which is, beyond doubt, in their vicinity, must, as soon as possible and if appropriately equipped, acknowledge receipt and inform a Rescue Coordination Center through a coast station or coast earth station (see §80.1115(a)(2)). However, a ship station receiving an HF distress alert must not acknowledge it but must observe the requirements of §80.1123, and must, if the alert is not acknowledged by a coast station within 3 minutes, relay the distress alert.
- (d) A ship station acknowledging receipt of a distress alert in accordance with paragraphs (b) or (c) of this section should:
- (1) Acknowledge receipt of the alert by using radiotelephony on the distress and safety traffic frequency in the band used for the alert;
- (2) If acknowledgement by radiotelephony of the distress alert received on the MF or VHF distress alerting frequency is unsuccessful, acknowledge receipt of the distress alert by responding with a digital selective call on the appropriate frequency.
- (e) A ship station in receipt of a shore-to-ship distress alert relay (see §80.1113(e)) should establish communication as directed and render such assistance as required and appropriate.

§80.1123 Watch requirements for ship stations.

- (a) While at sea, all ships must maintain a continuous watch:
- (1) On VHF DSC channel 70, if the ship is fitted with a VHF radio installation in accordance with \$80.1085(a)(2);
- (2) On the distress and safety DSC frequency 2187.5 kHz, if the ship is fitted with an MF radio installation in accordance with §§ 80.1089(a)(2) or 80.1091(a)(3);
- (3) On the distress and safety DSC frequencies 2187.5 kHz and 8414.5 kHz also on at least one of the distress and safety DSC frequencies 4207.5 kHz, 6312 kHz, 12577 kHz, or 16804.5 kHz appropriate to the time of day and the geographical position of the ship, if the ship is fitted with an MF/HF radio installation in accordance with

- §§ 80.1091(a)(2)(ii) or 80.1093(a) of this part (this watch may be kept by means of a scanning receiver limited to six distress and safety DSC frequencies); and
- (4) For satellite shore-to-ship distress alert, if the ship is fitted with an INMARSAT ship earth station in accordance with §80.1091(a)(1).
- (b) While at sea, all ships must maintain radio watches for broadcasts of maritime safety information on the appropriate frequency or frequencies on which such information is broadcast for the area in which the ship is navigating.
- (c) Until February 1, 1999, every ship while at sea must maintain, when practicable, a continuous listening watch on VHF Channel 16. This watch must be kept at the position from which the ship is normally navigated or at a position which is continuously manned.
- (d) Until February 1, 1999, every ship required to carry a radiotelephone watch receiver must maintain, while at sea, a continuous watch on the radiotelephone distress frequency 2182 kHz. This watch must be kept at the position from which the ship is normally navigated or at a position which is continuously manned.
- (e) On receipt of a distress alert transmitted by use of digital selective calling techniques, ship stations must set watch on the radiotelephone distress and safety traffic frequency associated with the distress and safety calling frequency on which the distress alert was received.
- (f) Ship stations with narrow-band direct printing equipment must set watch on the narrow-band direct-printing frequency associated with the distress alert signal if it indicates that narrow-band direct-printing is to be used for subsequent distress communications. If practicable, they should additionally set watch on the radiotelephone frequency associated with the distress alert frequency.

§80.1125 Search and rescue coordinating communications.

(a) The distress signal consists of the word MAYDAY, pronounced in radiotelephony as the French expression "M'aider". For distress traffic by radiotelephony, when establishing